

Houston, TX

Mount Airy, NC

Section 1: Identification

Product Identifier

Trade Name: B-24-035
Chemical Name: Polyurethane Resin
Recommended Use: Component for the manufacture of Polyurethanes
Restrictions on Use:

Chemical Manufacturer Information

Name: NCFI Polyurethanes
Address: 1515 Carter St Mount Airy, NC 27030
Website: www.NCFI.com

Phone: (800) 346-8229
Fax: (336) 789-9586
Emergency Phone: CHEMTREC: 800-424-9300

Section 2: Hazard Identification

Classification of the substance or mixture:

GHS Classification:	
• Skin irritation, Category 2	• Eye irritation, Category 2
• Respiratory irritation, Category 2	•

GHS Labeling:



Danger

Hazard Statements:	
• Causes eye and skin burns	• Harmful if swallowed
• Causes respiratory irritation	•

Precautionary Statements:	
• Do not breathe fume/gas/mist/vapors/spray	• Wear protective gloves/eye protection/face protection
• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	• IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
• IF ON SKIN: Wash with plenty of soap and water	

Other Hazards:

Section 3: Composition

Houston, TX

Mount Airy, NC

Hazardous Components

Type of product: Mixture

CAS#	Weight %	Name
Trade secret	< 5%	Tertiary Amine Catalysts
9046-10-0	28%	Polyoxypropylene Diamine

Section 4: First Aid Measures

Inhalation:	Move to fresh air if symptoms develop. If breathing is difficult, give oxygen and call physician.
Eye Contact:	Flush with water for at least 15 minutes. See a physician if irritation develops.
Ingestion:	Do not induce vomiting unless told to do so by a medical professional.
Most Important symptoms and effects, acute and delayed:	May cause skin or eye irritation upon contact. Avoid breathing vapors. The dense vapors can displace and reduce breathing air in confined or unventilated spaces causing asphyxiation. Overexposure may cause tremors, confusion, irritation, and may result in cardiac sensitization.
Indication of immediate medical attention and special treatment, if applicable:	N/A
Skin Contact:	Wash with soap and water at first opportunity.

Section 5: Fire-Fighting Measures

Suitable extinguishing media:	Water, dry chemicals, CO ₂
Unsuitable extinguishing media:	None
Special hazards arising from the chemical:	Overheated containers may rupture due to pressure produced by C ₄ H ₅ F ₅ /C ₃ HF ₇ . C ₄ H ₅ F ₅ /C ₃ HF ₇ burn to form acids and noxious gases.
Precautions for fire-fighters:	A self-contained breathing apparatus should be worn to protect against toxic and irritating vapors.

Section 6: Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures:	Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.
Environmental precautions:	Do not discharge into drains/surface waters/groundwater
Methods and material for containment and cleanup:	Absorb with sawdust, etc., and shovel into container. Waste material should be disposed of under conditions which meet federal, state, and local environmental regulations.

Section 7: Handling and Storage

Precautions for safe handling:	Store between 65°F and 95°F out of sunlight. Relieve pressure slowly when
---------------------------------------	---

Houston, TX

Mount Airy, NC

	opening container. Under no circumstances should empty drums be burned or cut open with an electric or gas torch.
Conditions for safe storage, including any incompatibilities:	Keep tightly sealed.

Section 8: Exposure Controls and PPE

Exposure Limits

Component:	Type	Value
Polyoxypropylene Diamine I	TWA	None established
Tertiary Amine Catalysts ¹	TWA	None established

¹Not listed as a carcinogen (NTA, IARC, OSHA)

Exposure Controls

Respiratory Protection:	The specific respirator selected must be based on contamination levels of this material found in the workplace and the working limits of the respirator. A supplied air, full-face mask, positive pressure or continuous flow respirator or a supplied air hood is required when airborne concentrations are unknown or exceed threshold limit values. A positive pressure, self-contained breathing apparatus can be used in emergencies or other unusual situations. Full-face air purifying respirators equipped with organic vapor cartridges can be used in certain situations, <i>see OSHA standard 29CFR 1910.134</i> . All equipment must be NIOSH approved and maintained.
Hand, eye, skin, body protection:	Wear goggles or chemical safety glasses and chemically resistant rubber or plastic gloves. Avoid eye and skin contact. Eye wash system and showers should be available.

Section 9: Physical and Chemical Properties

Basic chemical and physical properties

Appearance:	Liquid	Flammability:	N/A
Color:	Brown	Upper/lower flammability or explosive limits:	N/A
Odor:	Faint ammonia odor	Vapor pressure:	N/A
Odor threshold:	N/A	Vapor density:	N/A
pH:	N/A	Relative density:	1.057g/mL
Melting pt/freezing pt:	<32°F	Solubility(ies):	Highly soluble in water
Boiling pt/boiling range:	>150°F	Partition coefficient (n-octanol/water):	N/A
Flash point:	>200°F	Auto-ignition temperature:	>500°F
Evaporation rate:	Slower than ether	Decomposition temperature:	>500°F

Section 10: Stability and Reactivity

Chemical stability:	Stable
Possibility of hazardous reactions:	N/A
Conditions to avoid:	N/A

Houston, TX

Mount Airy, NC

Incompatible materials:	Isocyanates and other chemicals that react with hydroxyl groups.
Hazardous decomposition products:	When burned, CO, CO ₂ , NO _x aliphatic fragments, halogens, halogen acids, and possibly carbonyl halides

Section 11: Toxicological Information

Acute toxicity:	May cause skin irritation
Chronic toxicity:	Not available
Likely routes of exposure:	Skin
Symptoms related to physical, chemical and toxicological characteristics:	May cause skin irritation
Delayed and immediate effects and chronic effects from short and long-term exposure:	May cause skin irritation; avoid contact with eyes
Numerical toxicity measures:	Not available

Section 12: Ecological Information

Ecotoxicity:	Not a marine pollutant
Persistence and degradability:	No known significant effects
Bioaccumulative potential:	Does not bioaccumulate
Mobility in soil:	

Section 13: Disposal

Waste disposal:	R component drums can be sent to drum reconditioners or disposed of as ordinary industrial waste in compliance with pertinent regulations
------------------------	---

Section 14: Transport

UN number:	Not regulated
UN Proper shipping name:	Not regulated
Transport Hazard class(es):	Not regulated
Packing group, if applicable:	Not regulated
Marine pollutant (YorN):	N
Special precautions:	None

Section 15: Regulatory

Relevant safety, health, and environmental regulations

Inventory Status:	All components TSCA listed
US Regulations:	No ingredients listed



SAFETY DATA SHEET According to GHS

PO Box 1528 • Mount Airy, NC 27030-1528
800.346.8229 • Fax 336.789.9586 • www.NCFI.com

Houston, TX

Mount Airy, NC

US Superfund Amendments and Reauthorization Act (SARA)
Title III Section 313 information:

No ingredients listed

Section 16: Other

SDS Preparation Date:	02/18/2015
Revision Date:	10/31/2017
Revision Date:	6/26/2025

IMPORTANT NOTICES

This notification is a part of the Safety Data Sheet document and must not be detached. Any copying and redistribution of the Safety Data Sheet shall include copying of this notice and attaching the copy to the redistributed Safety Data Sheet copies.

This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of NCFI. The data on this sheet relates only to the specific material designated herein. NCFI assumes no legal responsibility for use or reliance upon these data.

APPLICATOR BULLETIN

JOBSITE SAFETY & VENTILATION

Houston, TX

Mount Airy, NC

1. ONLY TRAINED APPLICATOR PERSONNEL WEARING REQUIRED PERSONAL PROTECTIVE EQUIPMENT (PPE) SHOULD BE ALLOWED WITHIN 50 FEET OF THE SPRAY ZONE AND FOR 24 HOURS AFTER COMPLETION OF SPRAYING.
2. MARK THE AREA WITH WARNING TAPE AND SIGNAGE TO PREVENT UNPROTECTED PERSONS FROM ENTERING THE WORK ZONE. THIS INCLUDES THE AREA AT THE EXHAUST FAN OUTLET.
3. CREATE A VENTILATION PLAN FOR THE WORK ZONE. HOMEOWNERS SHOULD BE COMPLETELY EVACUATED DURING AND FOR 24 HOURS AFTER COMPLETION OF SPRAYING. LARGER STRUCTURES OR THOSE WITH MULTIPLE FLOORS CAN BE PARTITIONED AND ISOLATED WITH PLASTIC FILM SO THAT OTHER TRADES ON THE JOBSITE NOT WEARING PPE CAN CONTINUE TO WORK SAFELY.
4. MAKE SURE THAT IGNITION SOURCES AND HVAC SYSTEMS INCLUDING INLET VENTS ARE SHUT DOWN AND MASKED OFF TO PREVENT ACCIDENTAL USE DURING APPLICATION.
5. ACTIVE VENTILATION SHOULD BE USED WITH FAN(S) POSITIONED TO MAINTAIN A MINIMUM OF 30 ACH (AIR CHANGES/HOUR) TO EXHAUST VAPORS AND ODORS WHILE THE FOAM IS SAFELY CURED. VENTILATION PLANS WILL VARY ACCORDING TO SIZE OF THE SPACE, LAYOUT AND SCHEDULING.
6. FILTERS SHOULD BE USED OVER THE EXHAUST FAN INLET DURING SPRAYING TO PREVENT BUILDUP OF RESIDUE ON FAN BLADES WHICH WILL DECREASE AIR MOVEMENT SUBSTANTIALLY.
7. OPTIONAL INLET FANS CAN BE USED TO INCREASE AIR MOVEMENT, TAKING CARE THAT THE EXHAUST FAN IS MOVING AIR AT A GREATER RATE TO MAINTAIN NEGATIVE PRESSURE WITHIN THE SPRAY ZONE.
8. REFER TO NCFI PRODUCT STEWARDSHIP MANUAL, SFC GUIDANCE ON BEST PRACTICES FOR APPLICATION OF POLYURETHANE FOAM, www.sprayfoam.org AND EPA VENTILATION GUIDANCE www.epa.gov/dfe OR CALL NCFI AT 800-346-8229 FOR RECOMMENDATIONS BEFORE COMMENCING WORK.